





- 1Type
- DK

With triangle
- VK7

With square
- VK8

With square
- SCH





With slot
- VDE

With double bit
- 3Version of the hook
- H1

Pivoting radius R=28
- 5Identification no.
- 1

Without latch bracket
- 2

With latch bracket



2	Hook distance A	d	h
	18	28	4

* Dimensions of the latch bracket → Page XYZ

Specification	4
Lock housing	
Stainless steel AISI 303	N
Other parts	
Stainless steel AISI 304	
Protection class IP 65	
RoHS	
On request	
• Hook-type latches with other hook distance A	
• Hook with other pivoting radius R	
Accessory	Page
GN 119.2 Socket Keys	QVX
GN 120 Protective Caps	QVX
GN 120.1 Opening Handles	QVX

Hook-type latches GN 115.8 with hook and latch bracket are mainly used for sliding doors and flaps. The locking action is in radial direction to the axis of rotation, resulting in a wide variety of different uses. The hook-type latches GN 115.8 are supplied with loosely enclosed hook.

see also...	Page
GN 115.8 Hook-Type Latches (Operation with Stainless Steel-Operating Elements) QVX	
GN 115.8 Hook-Type Latches (Operation with Operating Elements, Zinc Die Casting) QVX	

Technical Information	
Construction and assembly instructions	QVX
Overview Latch Types	QVX
IP Protection Classes	QVX
Stainless Steel Characteristics	QVX

How to order	1Type
	2Hook distance A
	3Version of the hook
	4Material
	5Identification no.
GN 115.8-VK8-18-H1-N-1	