



elesa
Original design RE.G2

2 Bearing type

K Ball bearing

3 Type (bracket)

- B** Rigid bracket
- L** Swivel bracket with mounting plate
- LF** Swivel bracket with mounting plate, with total lock brake

4 Coding

M Medium version

1

d ₁	b	d ₂	h	l ₁	l ₂	Type B	Type L / LF	l ₃	m ₁	m ₂	Type B	Type L / LF	m ₃	r	Max. dynamic load capacity in N
100*	40	9	138	100	85	85	85	46	60	-	-	-	80	-	1800
125*	50	11	170	140	115	110	110	70	73	85	87	87	105	-	2300
160	50	11	205	140	115	110	110	70	73	85	87	87	105	126	3000
200	50	11	250	140	115	110	110	70	73	85	87	87	105	126	5000

* Only available in type B and type L

Specification

5

Wheel tread

- Natural rubber (NR)
- Black
- Hardness 70 Shore A

Wheel core

Aluminum die casting

Bracket

Steel sheet, zinc plated

ST

Swivel head bracket

- Dual grease-lubricated ball bearing
- Dust protection ring on type L / LF
- Plastic, polyethylene (PE)

Operating temperature -20 °C to +70 °C

RoHS

Technical Information

Page

Operating Conditions of Wheels and Casters	QVX
Technical Information for Wheels and Casters	QVX
Plastic Characteristics	QVX

Medium duty casters GN 22875 are used in industrial and public indoor and outdoor areas for moving medium weight carts, for example. The wheel tread is suitable for all floor types. It runs quietly and is gentle on floors while offering good obstacle clearing and vibration damping. The low wear on the ball bearing increases the service life, and the mounting to the inner ring can be accomplished with zero axial backlash.

see also...

Page

GN 22875 Wheels (without Bracket)	QVX
GN 22872 Medium Duty Casters (Wheel Tread Thermoplastic Elastomer)	QVX
GN 22873 Medium Duty Casters (Wheel Tread Rubber, Wheel Core Polypropylene)	QVX
GN 22874 Medium Duty Casters (Wheel Tread Rubber, Wheel Core Steel Sheet Metal)	QVX

How to order

1	d ₁
2	Bearing type
3	Type (bracket)
4	Coding
5	Material (bracket)

GN22875-160-K-LF-M-ST