



¹ l ₁	² d ₁	d ₃	d ₄	h ₁	h ₃	h ₄ Stroke	t min.
63	M 6	24	17,5	34,5	48,5	4	12,5
78	M 8	25	21	39,5	58,5	4	14
92	M 10	30	24	46,5	68,5	4	18
108	M 12	35	30	56,5	82	5	26,5

Specification

Handle

Zinc die casting

• Powder coated

- Black, RAL 9005, textured finish
- Black, RAL 9005, silk finish
- Orange, RAL 2004, textured finish
- Red, RAL 3000, textured finish
- Silver, RAL 9006, textured finish

• Chrome plated

- **SW**
- **SZ**
- **OS**
- **RS**
- **SR**
- **CR**

GN 300.4

Steel

- Axial bearing / Insert
Nitrided, blackened
- Retaining screw
Blackened

GN 300.7

Stainless steel

- Axial bearing
AISI 630
- Insert
AISI 420
- Retaining screw
AISI 304Cu

Pressure spring

Stainless steel AISI 301

RoHS

Adjustable hand levers GN 300.4 / GN 300.7 are produced with a clamping area which is linked via a thrust ball bearing (axial bearing) to the insert of the hand lever.

This has led to the following advantages:

- Doubled clamping force through vastly reduced friction.
- There is no movement on the contact area between adjustable hand lever and component which greatly reduces any marking on the clamping area.
- In addition a reduced creep factor has been achieved by the increased preload.

see also...

GN 6335.9 Hand Knobs (with Increased Clamping Force) Page QVX

Technical Information

Stainless Steel Characteristics QVX

How to order (Steel)

¹ ² ³
GN 300.4-78-M8-SW

1 l₁

2 d₁

3 Color (Finish)

How to order (Stainless steel)

¹ ² ³
GN 300.7-108-M12-SR

1 l₁

2 d₁

3 Color (Finish)