



4 Type
B Through-hole

1 d ₁	2 h					3 d ₂
15	12	15	20	-	-	6,5
20	15	20	25	30	-	8,5
25	15	20	25	30	40	10,5
30	20	30	40	-	-	13,5
40	20	30	40	50	-	13,5
50	30	40	50	-	-	17
60	30	60	-	-	-	17
80	30	40	50	80	-	21
100	30	40	80	-	-	21

Specification

Rubber

- Natural rubber (NR), black
- Operating temperature -40 °C to +80 °C
- Hardness Shore A ±5
 - Soft 40
 - Medium 55
 - Hard 70

RoHS

Rubber buffers GN 351 are suitable for the elastic mounting of machine units such as motors, compressors and pumps. Fastening can be carried out flexibly, e.g. with standard screws.

see also...	Page
GN 353 GN 453 Buffers	QVX

Technical Information

Overview of Types Vibration Damping Elements / Buffers / Rubber Buffers	QVX
Technical Instructions Buffers / Rubber Buffers	QVX
Resilent Characteristics GN 351 / GN 451	QVX
Plastic Characteristics	QVX

How to order		1	d ₁
		2	h
		3	d ₂
		4	Type
		5	Hardness
GN 351-30-20-13,5-B-70			