





Application example



- 4

Type
- D Cover plate on one side

1 d₁	2 h		3 d₂	s
20	15	-	8,5	2
25	20	-	10,5	2
30	30	-	13,5	2
40	10	-	10	2
40	20	30	13	2
50	40	-	17	2
60	30	-	17	2
60	50	-	21	2
60	20	30	21,5	2
80	30	-	21	3
80	35	40	25	3
100	40	-	21	3
100	25	-	22	3

Specification

Rubber

- Natural rubber (NR), black
- Vulcanized to the cover plate
- Operating temperature -40 °C to +80 °C
- Hardness Shore A ±5
 - Soft40
 - Medium55
 - Hard70

GN 351

Cover plate

Steel, zinc plated, blue passivated

GN 451

Cover plate

Stainless steel AISI 304
Only in hardness 55

RoHS

Rubber buffers GN 351 / GN 451 are suitable for the elastic mounting of machine units such as motors, compressors and pumps. Fastening can be carried out flexibly, e.g. with standard screws.

see also...	Page
GN 353 GN 453 Buffers	QVX

Technical Information

Overview of Types Vibration Damping Elements / Buffers / Rubber Buffers	QVX
Technical Instructions Buffers / Rubber Buffers	QVX
Resilient Characteristics GN 351 / GN 451	QVX
Plastic Characteristics	QVX
Stainless Steel Characteristics	QVX

How to order (Steel)	1 d ₁
	2 h
	3 d ₂
	4 Type
	5 Hardness
GN 351-60-50-21-D-40	

How to order (Stainless steel)	1 d ₁
	2 h
	3 d ₂
	4 Type
	5 Hardness
GN 451-100-40-21-D-55	