




4 Type

DD Cover plate on both sides

1 d ₁	2 h					3 d ₂	s
15	25	-	-	-	-	6	2
20	25	-	-	-	-	6	2
25	20	-	-	-	-	6,6	2
30	15	-	-	-	-	16	2
35	15	-	-	-	-	19	2
35	20	-	-	-	-	13	2
40	20	28	30	35	40	13	2
50	15	20	30	50	-	21	2
50	20	30	40	50	-	17	2
50	25	-	-	-	-	11	2
50	30	-	-	-	-	10	2
60	13	-	-	-	-	20,5	2
60	30	-	-	-	-	10,5	2
60	30	-	-	-	-	18	2
60	30	-	-	-	-	21,5	2
60	50	-	-	-	-	21	2
75	30	55	-	-	-	25	3
100	50	-	-	-	-	30	3
100	60	-	-	-	-	21	3

Specification

Rubber

- Natural rubber (NR), black
- Vulcanized to the cover plates
- Operating temperature -40 °C to +80 °C
- Hardness Shore A ±5

- Soft 40
- Medium 55
- Hard 70

GN 351

Cover plates

Steel, zinc plated, blue passivated

GN 451

Cover plates

Stainless steel AISI 304
Only in hardness 55

RoHS

Rubber buffers GN 351 / GN 451 are suitable for the elastic mounting of machine units such as motors, compressors and pumps. Fastening can be carried out flexibly, e.g. with standard screws.

Technische Informationen		Page
Overview of Types Vibration Damping Elements / Buffers / Rubber Buffers		QVX
Technical Instructions Buffers / Rubber Buffers		QVX
Resilient Characteristics GN 351 / GN 451		QVX
Plastic Characteristics		QVX
Stainless Steel Characteristics		QVX

How to order (Steel)		1 d ₁
		2 h
		3 d ₂
		4 Type
		5 Hardness
GN 351-50-30-10-DD-70		

How to order (Stainless steel)		1 d ₁
		2 h
		3 d ₂
		4 Type
		5 Hardness
GN 451-75-55-25-DD-55		