



**elesa**  
Original design VRTP-P+IR-SST



**2 Bore code**

- B** Without keyway
- K** With keyway

**4 Type**

- R** With revolving handle

**1**

**3**

d <sub>1</sub>	d <sub>2</sub> H7	d <sub>3</sub>	d <sub>4</sub>	d <sub>5</sub>	b	l <sub>1</sub>	l <sub>2</sub>	l <sub>3</sub>	r	Ø Handle
80	8	18	20,5	25	18	17	35	45	29	15,5
100	10	18	20,5	25,5	20	17	37	60	37	18
125	12	22	26	31	22	22	44	65	48	22
160	14	26	31	40	25	27	51	73	65	23
200	16	30	36	48,5	28	34	61	80	84	24

**Specification**

- Plastic  
Technopolymer (Polypropylene PP)
  - Reinforced, shock-resistant
  - Temperature resistant up to 80 °C
  - Black, matte finish
- Hub bushing  
Stainless steel AISI 304
- Hub cover
  - Stainless steel AISI 304
  - Self-adhesive
- Retractable handle
  - Plastic, Technopolymer (Polyamide PA)
  - Black, matte finish
  - Certified in accordance with FDA
  - Retracting mechanism  
Stainless steel AISI 304
- *Keyway P9 DIN 6885 Page 1 → Page 2078*
- *ISO Fundamental Tolerances → Page 2151*
- *Cross Holes GN 110 → Page 2080*
- *Plastic Characteristics → Page 2158*
- *Stainless Steel Characteristics → Page 2166*
- **RoHS**

**Information**

Elegant design taking account of ergonomic and hygienic requirements are the outstanding features of the handwheels with retractable handle GN 522.6.

Owing to the materials used, they are especially suitable for use in corrosive atmospheres or in areas which must be wet cleaned. In particular, the FDA certified plastic materials allow the use in the food industry.

The handle in these handwheels is locked in the bore. To tilt, first pull the handle out of the cone in axial direction.

A pressure spring keeps the handle in both positions. When folding out, it will automatically engage again.

**see also...**

- *Stainless Steel Countersunk Washers GN 184.5 (for Axial Fixing)*  
→ Page 1090

**How to order**

<b>1</b>	d <sub>1</sub>
<b>2</b>	Bore code
<b>3</b>	d <sub>2</sub>
<b>4</b>	Type

**GN 522.6-125-K12-R**

1.1  
1.2  
1.3  
1.4  
2.1  
2.2  
2.3  
2.4