



STAIN  
LESS  
\*\*

1

d <sub>1</sub>	d <sub>2</sub>	d <sub>3</sub>	l <sub>1</sub>	l <sub>2</sub>	l <sub>3 min.</sub>	l <sub>4</sub>	l <sub>5</sub>
M 6	14	6	60	50	15	15	45
M 8	14	6	60	55	17,5	15	45
M 10	18	8	80	60	20	17	63
M 12	20	10	100	70	25	19	81
M 16	24	13	120	85	35	23	97
M 20	30	16	140	95	40	28	112

**Specification**

**Tommy nut**

- Steel —
- Property class 5
- Blackened
- Stainless Steel AISI 304 **NI**

**Bar end caps**

Plastic, Polyethylen (PE)  
Gray

**Pressure spring**

Stainless steel AISI 301

RoHS

2

Tommy nuts DIN 6307 are used for clamping and locking.

The sliding bar is protected against loss by the end caps and held in any position by the pressure spring.

**see also...**

	Page
<b>DIN 6305 Tommy Nuts (with Fixed Bar)</b>	ganternorm.com

**Technical Information**

Strength Values of Nuts	2395
Stainless Steel Characteristics	2422

**How to order (Steel)**

<b>DIN 6307-M12</b>	1 d <sub>1</sub>
---------------------	------------------

**How to order (Stainless Steel)**

<b>DIN 6307-M16-NI</b>	1 d <sub>1</sub>
	2 Material

1.1

1.2

1.3

1.4

2.1

2.2

2.3

2.4

