


STAINLESS *
*

- 3 Type**
 - B Without rest position
 - C With rest position
- 4 Coding**
 - R Standard thread
 - F Fine thread



1 d_1	2 l_1	d_2		d_3	l_2	l_3	l_4	$l_5 \approx$	$l_6 \approx$	$l_7 \approx$	A/F
Plunger h9 Bore $+0,08$ $+0,03$		Coding R	Coding F								
4	5	M 10	M 10 x 1	17	8	20	26	2	30	47	15
5	5	M 10	M 10 x 1	17	8	20	26	2	30	47	15
6	7	M 12	M 12 x 1,5	22	10	27	35	3	40	63	19
7	7	M 12	M 12 x 1,5	22	10	27	35	3	40	63	19
8	10	M 16	M 16 x 1,5	26	12	33	43	3	51	78	22
10	10	M 16	M 16 x 1,5	26	12	33	43	3	51	78	22

Specification

- Guide**
 - Steel **ST**
 - Zinc plated, blue passivated
 - Stainless steel AISI 303 **NI**

Plunger pin
Stainless steel AISI 303

- Lever**
 - Plastic, polyphthalamide (PPA)
 - Glass fiber reinforced
 - Black **SW**

Pressure spring
Stainless steel AISI 202

RoHS

Technical Information **Page**

Overview of Indexing Plungers	QVX
Load Rating Information	QVX
Metric ISO Fine Thread DIN 13	QVX
ISO Fundamental Tolerances	QVX
Stainless Steel Characteristics	QVX

Indexing plungers GN 823 with operating lever can be used to lock carriages in guides, for example. The plunger is retracted by simply pressing the operating lever.

Type C also allows actuation by pulling and locking the plunger pin in the retracted position (rest position).

see also... **Page**

GN 823 Indexing Plungers (with Operating Lever, with Flange for Surface Mounting)	QVX
GN 822.6 Mini Indexing Plungers (Steel, with Knob)	QVX
GN 822.7 Mini Indexing Plungers (Stainless Steel, with Knob)	QVX

Accessory

GN 412.2 GN 412.4 Positioning Bushings (with Collar)	QVX
GN 412.3 GN 412.5 Positioning Bushings (with Ramping Cone)	QVX
GN 609.5 Distance Bushings (Stainless Steel)	QVX
GN 412.1 Mounting Blocks (Zinc Die Casting)	QVX
GN 612.1 Mounting Blocks (Steel)	QVX
GN 909 GN 909.5 Thin Hex Nuts	QVX

How to order

1 d_1
2 l_1
3 Type
4 Coding
5 Material
6 Color

GN 823-10-10-B-R-NI-SW