

CLA

STRAIGHT GUIDE PILLAR

FÜHRUNGSSÄULE | COLONNA LISCIA

DIN 9825 / ISO 9182-2



Material: 1.7131 Hardness: 61 + 63 HRC Execution: superfinished	 DAYS 12	3D-CAD 	 HOW TO ORDER CLA * D1 * L (CLA1590)
--	----------------	-------------------	--



D1	L																		
	90	100	112	125	140	160	180	200	224	250	280	315	355	400	450	500	600	700	800
15 - 16	◇	◇	◇	◇	◇	◇	◇	◇	◇	◇									
19 - 20		◇	◇	◇	◇	◇	◇	◇	◇	◇									
24 - 25		◇	◇	◇	◇	◇	◇	◇	◇	◇	◇	◇	◇	◇	◇	◇			
30 - 32				◇	◇	◇	◇	◇	◇	◇	◇	◇	◇	◇	◇	◇			
38 - 40						◇	◇	◇	◇	◇	◇	◇	◇	◇	◇	◇			
48 - 50								◇	◇	◇	◇	◇	◇	◇	◇	◇			
60 - 63										◇	◇	◇	◇	◇	◇	◇			
80											◇	◇	◇	◇	◇	◇	◇	◇	◇