











Toggle Clamps				
Standard	**Properties**	**Kinematics**	**Clamping force F_S** in N at 6 bar	**Holding capacity F_H** in N
GN 860 Page XYZ	- Knee lever principle - The tensioning mechanism corresponds to the manually operated toggle clamps in terms of design - End position detection		380...3200	700...4000
GN 861 Page XYZ	- Knee lever principle - Heavy duty design with high clamping forces - End position detection		2500...3600	10000...20000
GN 862 Page XYZ	- Knee lever principle - Mounting via angled base - End position detection		570...1800	750...2600
GN 862.1 Page XYZ	- Knee lever principle - Mounting via angled base - Design and dimensions as GN 862, however with additional manual operation - End position detection		870...2280	2200...8500
GN 863 Page XYZ	- Knee lever principle - Mounting via angled base - Heavy duty design with high clamping forces - End position detection		1260...1800	2200...2600
GN 890 Page XYZ	- Knee lever principle - The tensioning mechanism corresponds to the manually operated push-pull type toggle clamps in terms of design - for push clamping - End position detection		3250...5600	10000...20000
GN 962 Page XYZ	- Knee lever principle - Mounting via angled base - Heavy duty design with high clamping forces - „Longlife“ - End position detection		780...5520	1200...25000

Power Clamps

Standard	Properties	Kinematics	Clamping force F_S in N at 6 bar	Holding capacity F_H in N
GN 864 Page XYZ	- Dead point mechanism - Clamping arm horizontal, vertical, or centered - High clamping forces - Compact size - Low air consumption - Long service life - End position detection		2220...9000	4070...13300
GN 865 Page XYZ			1250...4900	2300...7200
GN 866 Page XYZ			630 ...1800	1150...2000

Swing Clamps

Standard	Properties	Kinematics	Clamping force F_S in N at 6 bar	Holding capacity F_H in N
GN 875 Page XYZ	- Pivot and linear motion - In block version, universal mounting capability - Compact dimensions - End position detection		170 ...1100	170...1100
GN 876 Page XYZ	- Pivot and linear motion - With screw-in thread, adjustable - Compact dimensions		170 ...1100	170...1100